For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

HES Series Garden Hose Dishwasher Fitting – Female Hose Thread x Compression

Use: To connect Whirlpool, Maytag, Amana, Kitchen Aid, and Jenn-Air dishwashers manufactured after September 2009 to flexible water connector. All female hose thread connections require a rubber washer inserted prior to installation.

Design Features:

- One-piece brass body provides strength, durability, and longer-lasting performance
- Swivel hose thread nut simplifies fitting alignment to make the water connector installation quick and easy
- High-temperature resistant washer for a reliable, longer-lasting performance



Operating Specifications:

40° to 140° F, intermittent to 180° F Temperature:

125 PSI maximum Working Pressure:

Low-lead Product

FITTING MATERIAL SPECIFICATIONS		
Body	Low-lead brass	
Hose Nut	Low-lead brass	
Hose Washer	Rubber	

PART DIMENSIONS (Inches)				
Model	DIM. A	DIM. B		
HES-6-12X	1.43	1.25		
HES-8-12X	1.43	1.25		
HES6-12WNMX	1.43	1.25		

Low-lead Part Listing:

HES-6-12X	3/4" female hose thread, swivel x 3/8" OD compression, rough brass
HES-6-12X B	3/4" female hose thread, swivel x 3/8" OD compression, rough brass, bulk
HES-6-12X D	3/4" female hose thread, swivel x 3/8" OD compression, rough brass, carded
HES-6-12WNMX	3/4" female hose thread, swivel x 3/8" OD compression, w/ nut and sleeve, rough brass,
	carded
HES-8-12X	3/4" female hose thread, swivel x 1/2" OD compression, rough brass