



Brisa 2000

Designed in 2000

	Safety cage compatible
	Proudly assembled with American labor
	Handmade

shown in Polished Copper with wood blades



shown in Textured Bronze with wood blades

Like satellites orbiting a planet, the Brista's select mahogany blade head and lunar counterweight gently revolve 360° about its spherical gear housing. The fan head can be infinitely positioned in a 180-degree arc for optimum air movement; the greater the angle of the motor to the horizontal support rods (up or down), the faster the axial rotation. A slow, controlled axial rotation is achieved by both fan head position and fan blade speed. Matthews 360° rotational fans circulate heat and air conditioning more efficiently than traditional paddle fans. Constructed of cast aluminum, heavy spun and stamped steel, the Brista carries a limited lifetime warranty.

Current specification sheets can be found at MatthewsFanCo.com. (08_2019)

Matte Black	Bronze (Plate)	Bronzette (Powdercoat)
Brushed Nickel	Polished Chrome	Polished Copper

Standard Finishes

Brushed Brass	Polished Brass	Agua Marinha	Safira	Ametista	Ouro
Brushed Copper	Polished Chrome Damp	Jade	Esmeralda	Rubi	Black Nickel
Brushed Nickel Damp	Gloss White				

Special Order Finishes

Brisa 2000

TECHNICAL SPECIFICATIONS

FAN SPECIFICATIONS

Fan Weight	21 lbs
Voltage	110 or 220
Motor Type	AC
Downrods Lengths Field cuttable. Non-threaded	inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183
Downrod Diameter	.75 inch
Overall Drop	10 inches / 25 cm + downrod length
Environment	Damp location with protective powder or clear coat only. Neither coastal, saltwater nor chlorine compatible.
Ambience	Soothing White Noise
Safety Certification	UL / CUL
Warranty	Limited Lifetime

NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA

Fan Head Options	Solid Mahogany Wood ¹	Metal with Guard
Fan Diameter	40 inches / 102 cm	39 inches / 99 cm
Fan Blade Diameter	16 inches / 41 cm	13 inches / 33 cm
Guard Options	No Cage Option	Decorative Cage or Safety Cage with tight fines ²
Blade Pitch	19°	31°
CFM (Low / High)	1602 / 2376	790 / 1265
RPM (Low / High)	866 / 1336	790 / 1205
Watts (High)	52.44	55.15
CFM / Watt (High)	45.31	22.94

SKU NAMING CONVENTION

SKU#	B2K-XX-XXX (Model+Finish+Fan Blade)	
Standard Finishes	Black	— BK
	Bronze	— BZ
	Bronzette	— BZZT
	Brushed Nickel	— BN
	Polished Chrome	— CR
Special Order	Polished Copper	— CP
	Brushed Brass	— BRBR
	Polished Brass	— PB
	Brushed Copper	— BRCP
	Polished Chrome Damp	— CRDAMP
	Brushed Nickel Damp	— BNDAMP
	Gloss White	— WH
	Agua Marinha	— LTBLUE
	Saffra	— BLUE
	Ametista	— LTPURPLE
Ouro	— GOLD	
Jade	— LTGREEN	
Esmeralda	— GREEN	
Rubi	— RED	
Black Nickel	— BKN	
Fan Blade	Wood Blade	— WD
	Metal Blade	— MTL


¹ Matthews' Brazilian mahogany is ecologically harvested.
² Safety cages with tight fines are for use in low ceiling applications: 7 ft in USA and 8.2 ft in Canada

STANDARD EQUIPMENT

One downrod of 10 inches / 13 cm


Flat ceiling canopy

Decora-style, 3-speed wall control in white



OPTIONAL EQUIPMENT

29° vaulted ceiling mount and canopy



CEILING PITCH TABLE

0/12	0 degrees
1/12	4.76 degrees
2/12	9.46 degrees
3/12	14.04 degrees
4/12	18.43 degrees
5/12	22.62 degrees
6/12	26.57 degrees
7/12	30.26 degrees
8/12	33.69 degrees
9/12	36.87 degrees
10/12	39.81 degrees
11/12	42.51 degrees

CEILING HEIGHT / DOWNROD TABLE

Ceiling Height	Downrod Lengths Field cuttable Non-threaded
10 ft or less	5 inches / 13 cm <i>Use safety cage if applicable</i>
10 -12 feet	10 inches / 25 cm
13 feet	20 inches / 51 cm
14 feet	30 inches / 76 cm
15 feet	48 inches / 122 cm
16 feet +	72 inches / 183 cm



Matthews Fan Company

1881 Industrial Drive
 Libertyville, IL 60048
 Tele: 847.680.9043
 Fax: 847.680.8140
 www.matthewsfanco.com

© 2019 Matthews Fan Company. All rights reserved.