

SPECIFICATION SHEET



TWO HANDLE LAVATORY WIDESPREAD FAUCET



**Model #:** \_\_\_\_\_  
**Specific Features:** \_\_\_\_\_  
**Project Name:** \_\_\_\_\_  
**Submitted For:** \_\_\_\_\_  
**Date:** \_\_\_\_\_

- Lever Handles
- J Style Rigid Spout
- 4-3/4" Reach, 3-11/16" From Deck to Aerator
- Ceramic Disc Cartridges
- 3-Hole 4" to 12" Installation
- Brass Pop-Up Drain Assembly
- With 1.2 GPM Flow Rate
- With 0.5 GPM Flow Rate Aerator Available upon request

# L-7472 SHOWN **ADA**

Model #	Features	Finish	
L-7472*		CP	
L-7472-BN*		PVD BN	
L-7472-ORB*		ORB	
L-7472-E0.5	With 0.5 GPM Aerator	CP	

Olympia products are engineered and manufactured to meet the following standards and codes:

ASME A112.18.1  
 ANSI A117.1  
 ANSI / NSF 61, SECTION 9  
 CONTAINS NO MORE THAN 0.25% WEIGHTED AVERAGE LEAD CONTENT

\* Aerator limited to 1.2 GPM Flow Rate  
 \* E0.5 - 0.5 GPM Flow Rate Aerator Available upon request

Note:  
 Optional 2" Shank  
 Extension Kit (OP-  
 490030) Available.

