

Project:

REALS LED Surface Mount Spec Sheet

SKU: 7309.XX.DL.74-WL Learn more at: https://sonnemanlight.com/reals-led-surface-mount

Description: REALS surface-mounted lights are neatly compact and solidly built. They offer a range of lens variations within the tightly defined geometry of their die-cast rings. Also available as a Downlight Sconce, Up/Down Sconce, Bollard, and Double Bollard.

Type #:



Dimensions

Height: 3.25"
Diameter: 5"
Canopy/Backplate/Base: 5"

Electrical Specs

Bulb(s) Included?: Yes Bulb 1 Type: Integral LED Bulb Quantity: Input Voltage: 120VAC Wattage: 10 Initial Lumens: 1040 Color Temperature: 3000K CRI: 90 Power Supply Type: Driver Power Supply Quantity: Power Supply Location: **Outlet Box** Dimming Type: TRIAC/ELV Bulb Max Wattage: 10

Installation

Installation: Licensed electrician required

Shipping

 Carton 1 L x W x H:
 9" X 9" X 6"

 Carton 1 Gross Weight:
 3 LBS

 Fixture Weight:
 2

Shade

Lens Type: Dome Lens
Shade 1 Material: Frosted
White
Polycarbonat

Available Finishes

Available Finishes: Textured Bronze (.72), Textured Gray (.74), Textured White (.98)

General Listings

Features: Wet Rated
Certification: C-ETL-US
Color/Finish: Textured
Gray (.74)
Dark Sky Friendly: N