

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Solo Fixed Rail

Ceiling and Wall Mount

Model & Size	Color Temp & CRI	Lumens	Finish
TK-180503 3 Light TK-180504 4 Light	3000K 90	2400 3200	BK Black BN Brushed Nickel WT White

Example: **TK-180503-30-BK**

DESCRIPTION

Designed for residential and low-ceiling commercial applications, the Solo fixed rail has a wide multitude of applications, from ceiling to bath vanity.

FEATURES


- Multiple LED array for uniform illumination
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum
Power:	32W, 24W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
	3 Step Mac Adam Ellipse
Lens:	Frosted TIR Lens
Rated Life:	50000 Hours
Mounting:	Installs over a 3" or 4" Junction Box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically Powder Coated:White, Electrostatically Powder Coated::Black, Electrostatically Powder Coated::Brushed Nickel, Electrostatically Powder Coated:Black, Electrostatically Powder Coated::White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Damp Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant, ADA



FINISHES:



LINE DRAWING:

